



ÉCOLE POLYTECHNIQUE  
FÉDÉRALE DE LAUSANNE

# Spark SQL

Big Data Analysis with Scala and Spark

Heather Miller

# Relational Databases

*SQL is the lingua franca for doing analytics.*

# Relational Databases

*SQL is the lingua franca for doing analytics.*

But it's a pain in the neck to connect big data processing pipelines like Spark or Hadoop to an SQL database.

**Wouldn't it be nice...**

- ▶ if it were possible to seamlessly intermix SQL queries with Scala?
- ▶ to get all of the optimizations we're used to in the databases community on Spark jobs?

# Relational Databases

*SQL is the lingua franca for doing analytics.*

But it's a pain in the neck to connect big data processing pipelines like Spark or Hadoop to an SQL database.

**Wouldn't it be nice...**

- ▶ if it were possible to seamlessly intermix SQL queries with Scala?
- ▶ to get all of the optimizations we're used to in the databases community on Spark jobs?

**Spark SQL delivers both!**

# Spark SQL: Goals

Three main goals:

1. Support **relational processing** both within Spark programs (on RDDs) and on external data sources with a friendly API.

*Sometimes it's more desirable to express a computation in SQL syntax than with functional APIs and vice a versa.*

# Spark SQL: Goals

Three main goals:

1. Support **relational processing** both within Spark programs (on RDDs) and on external data sources with a friendly API.
2. High performance, achieved by using techniques from research in databases.
3. Easily support new data sources such as semi-structured data and external databases.

# Spark SQL

**Spark SQL is a component of the Spark stack.**

- ▶ It is a Spark module for structured data processing.
- ▶ It is implemented as a library on top of Spark.

# Spark SQL

**Spark SQL is a component of the Spark stack.**

- ▶ It is a Spark module for structured data processing.
- ▶ It is implemented as a library on top of Spark.

**Three main APIs:**

- ▶ **SQL literal syntax**
- ▶ **DataFrames**
- ▶ **Datasets**



# Spark SQL

**Spark SQL is a component of the Spark stack.**

- ▶ It is a Spark module for structured data processing.
- ▶ It is implemented as a library on top of Spark.

**Three main APIs:**

- ▶ **SQL literal syntax**
- ▶ **DataFrames**
- ▶ **Datasets**

**Two specialized backend components:**


- ▶ **Catalyst**, query optimizer.
- ▶ **Tungsten**, off-heap serializer.

# Spark SQL

**Spark SQL is a component of the Spark stack.**

- ▶ It is a Spark module for structured data processing.
- ▶ It is implemented as a library on top of Spark.

**Visually, Spark SQL relates to the rest of Spark like this:**




# Spark SQL

**Spark SQL is a component of the Spark stack.**

- ▶ It is a Spark module for structured data processing.
- ▶ It is implemented as a library on top of Spark.

**Visually, Spark SQL relates to the rest of Spark like this:**




# Spark SQL

**Spark SQL is a component of the Spark stack.**

- ▶ It is a Spark module for structured data processing.
- ▶ It is implemented as a library on top of Spark.

**Visually, Spark SQL relates to the rest of Spark like this:**



# Relational Queries (SQL)

Everything about SQL is structured.

In fact, SQL stands for *structural query language*.

- ▶ There are a set of fixed data types. Int, Long, String, etc.
- ▶ There are fixed set of operations. SELECT, WHERE, GROUP BY, etc.

Research and industry surrounding relational databases has focused on exploiting this rigidness to get all kinds of performance speedups.

# Relational Queries (SQL)

Everything about SQL is structured.

In fact, SQL stands for *structural query language*.

- ▶ There are a set of fixed data types. Int, Long, String, etc.
- ▶ There are fixed set of operations. SELECT, WHERE, GROUP BY, etc.

Research and industry surrounding relational databases has focused on exploiting this rigidness to get all kinds of performance speedups.

*Let's quickly establish a common set of vocabulary and a baseline understanding of SQL.*

# Relational Queries (SQL)


Data organized into one or more **tables**

Customer_Name	Destination	Ticket_Price
"Weitz"	"Luzern"	53.20
"Schinz"	"Zürich"	32.40
"Dubois"	"Neuchâtel"	12.50
"Hug"	"Basel"	32.10
"Strub"	"Winterthur"	9.60
"Chapuis"	"Lausanne"	6.60
"Smith"	"Genève"	12.70
"Weitz"	"Bern"	21.40

# Relational Queries (SQL)

Data organized into one or more **tables**

- ▶ Tables contain **columns** and **rows**.



Customer_Name	Destination	Ticket_Price
"Weitz"	"Luzern"	53.20
"Schinz"	"Zürich"	32.40
"Dubois"	"Neuchâtel"	12.50
"Hug"	"Basel"	32.10
"Strub"	"Winterthur"	9.60
"Chapuis"	"Lausanne"	6.60
"Smith"	"Genève"	12.70
"Weitz"	"Bern"	21.40




# Relational Queries (SQL)

Data organized into one or more **tables**

- ▶ Tables contain *columns* and rows.

**rows**



Customer_Name	Destination	Ticket_Price
"Weitz"	"Luzern"	53.20
"Schinz"	"Zürich"	32.40
"Dubois"	"Neuchâtel"	12.50
"Hug"	"Basel"	32.10
"Strub"	"Winterthur"	9.60
"Chapuis"	"Lausanne"	6.60
"Smith"	"Genève"	12.70
"Weitz"	"Bern"	21.40

# Relational Queries (SQL)

Data organized into one or more **tables**

- ▶ Tables contain *columns* and *rows*.
- ▶ Tables typically represent a collection of objects of a certain type, such as **customers** or **products**

**SBB customers dataset**

Customer_Name	Destination	Ticket_Price
"Weitz"	"Luzern"	53.20
"Schinz"	"Zürich"	32.40
"Dubois"	"Neuchâtel"	12.50
"Hug"	"Basel"	32.10
"Strub"	"Winterthur"	9.60
"Chapuis"	"Lausanne"	6.60
"Smith"	"Genève"	12.70
"Weitz"	"Bern"	21.40


# Relational Queries (SQL)

Data organized into one or more **tables**

- ▶ Tables contain *columns* and *rows*.
- ▶ Tables typically represent a collection of objects of a certain type, such as **customers** or **products**

*A relation* is just a table.

*Attributes* are columns.



Customer_Name	Destination	Ticket_Price
"Weitz"	"Luzern"	53.20
"Schinz"	"Zürich"	32.40
"Dubois"	"Neuchâtel"	12.50
"Hug"	"Basel"	32.10
"Strub"	"Winterthur"	9.60
"Chapuis"	"Lausanne"	6.60
"Smith"	"Genève"	12.70
"Weitz"	"Bern"	21.40

# Relational Queries (SQL)

Data organized into one or more **tables**

- ▶ Tables contain *columns* and *rows*.
- ▶ Tables typically represent a collection of objects of a certain type, such as **customers** or **products**

A *relation* is just a table.

*Attributes* are columns.

Rows are *records* or *tuples*

**record  
/tuple**

Customer_Name	Destination	Ticket_Price
"Weitz"	"Luzern"	53.20
"Schinz"	"Zürich"	32.40
"Dubois"	"Neuchâtel"	12.50
"Hug"	"Basel"	32.10
"Strub"	"Winterthur"	9.60
"Chapuis"	"Lausanne"	6.60
"Smith"	"Genève"	12.70
"Weitz"	"Bern"	21.40

# Spark SQL

DataFrame is Spark SQL's core abstraction.

*Conceptually equivalent to a table in a relational database.*

*DataFrame, is a table, sort of.*

Customer_Name	Destination	Ticket_Price
"Weitz"	"Luzern"	53.20
"Schinz"	"Zürich"	32.40
"Dubois"	"Neuchâtel"	12.50
"Hug"	"Basel"	32.10
"Strub"	"Winterthur"	9.60
"Chapuis"	"Lausanne"	6.60
"Smith"	"Genève"	12.70
"Weitz"	"Bern"	21.40

# Spark SQL

**DataFrame** is Spark SQL's core abstraction.

*Conceptually equivalent to a table in a relational database.*

DataFrames are, *conceptually*, RDDs full of records with a known schema

*distributed collection of rows/records.*

*DataFrame, is a table, sort of.*

Customer_Name	Destination	Ticket_Price
"Weitz"	"Luzern"	53.20
"Schinz"	"Zürich"	32.40
"Dubois"	"Neuchâtel"	12.50
"Hug"	"Basel"	32.10
"Strub"	"Winterthur"	9.60
"Chapuis"	"Lausanne"	6.60
"Smith"	"Genève"	12.70
"Weitz"	"Bern"	21.40

# Spark SQL

**DataFrame** is Spark SQL's core abstraction.

*Conceptually equivalent to a table in a relational database.*

DataFrames are, *conceptually*, RDDs full of records **with a known schema**

Unlike RDDs though, DataFrames require some kind of schema info!

*DataFrame, is a table, sort of.*

Customer_Name	Destination	Ticket_Price
"Weitz"	"Luzern"	53.20
"Schinz"	"Zürich"	32.40
"Dubois"	"Neuchâtel"	12.50
"Hug"	"Basel"	32.10
"Strub"	"Winterthur"	9.60
"Chapuis"	"Lausanne"	6.60
"Smith"	"Genève"	12.70
"Weitz"	"Bern"	21.40

# Spark SQL

**DataFrame** is Spark SQL's core abstraction.

*Conceptually equivalent to a table in a relational database.*

DataFrames are, *conceptually*, RDDs full of records with a known schema

DataFrames are **untyped!** !!

*That is, the Scala compiler doesn't check the types in its schema!*

*DataFrames contain Rows which can contain any schema.*

*DataFrame, is a table, sort of.*

Customer_Name	Destination	Ticket_Price
"Weitz"	"Luzern"	53.20
"Schinz"	"Zürich"	32.40
"Dubois"	"Neuchâtel"	12.50
"Hug"	"Basel"	32.10
"Strub"	"Winterthur"	9.60
"Chapuis"	"Lausanne"	6.60
"Smith"	"Genève"	12.70
"Weitz"	"Bern"	21.40

RDD[T]

DataFrame



# Spark SQL

**DataFrame** is Spark SQL's core abstraction.

*Conceptually equivalent to a table in a relational database.*

DataFrames are, *conceptually*, RDDs full of records with a known schema

DataFrames are **untyped**!

*That is, the Scala compiler doesn't check the types in its schema!*

Transformations on DataFrames are also known as **untyped transformations**

*DataFrame, is a table, sort of.*

Customer_Name	Destination	Ticket_Price
"Weitz"	"Luzern"	53.20
"Schinz"	"Zürich"	32.40
"Dubois"	"Neuchâtel"	12.50
"Hug"	"Basel"	32.10
"Strub"	"Winterthur"	9.60
"Chapuis"	"Lausanne"	6.60
"Smith"	"Genève"	12.70
"Weitz"	"Bern"	21.40

# Creating DataFrames

DataFrames can be created in two ways:

1. From an existing RDD.  
*Either with schema inference, or with an explicit schema.*
2. Reading in a specific **data source** from file.  
*Common structured or semi-structured formats such as JSON.*

# Creating DataFrames

## (1a) Create DataFrame from RDD, schema reflectively inferred

Given pair RDD, RDD[(T1, T2, ... TN)], a DataFrame can be created with its schema automatically inferred by simply using the toDF method.

```
val tupleRDD = ... // Assume RDD[(Int, String String, String)]  
val tupleDF = tupleRDD.toDF("id", "name", "city", "country") // column names
```

*Note: if you use toDF without arguments, Spark will assign numbers as attributes (column names) to your DataFrame.*

\_1 \_2 \_3

# Creating DataFrames

## (1a) Create DataFrame from RDD, schema reflectively inferred



Given pair RDD, RDD[(T1, T2, ... TN)], a DataFrame can be created with its schema automatically inferred by simply using the toDF method.

```
val tupleRDD = ... // Assume RDD[(Int, String String, String)]  
val tupleDF = tupleRDD.toDF("id", "name", "city", "country") // column names
```

*Note: if you use toDF without arguments, Spark will assign numbers as attributes (column names) to your DataFrame.*

If you already have an RDD containing some kind of case class instance, then Spark can infer the attributes from the case class's fields.

```
case class Person(id: Int, name: String, city: String)  
val peopleRDD = ... // Assume RDD[Person]  
val peopleDF = peopleRDD.toDF
```



# Creating DataFrames

## (1b) Create DataFrame from existing RDD, schema explicitly specified

Sometimes it's not possible to create a DataFrame with a pre-determined case class as its schema. For these cases, it's possible to explicitly specify a schema.

It takes three steps:

- ▶ Create an RDD of Rows from the original RDD.
- ▶ Create the schema represented by a StructType matching the structure of Rows in the RDD created in Step 1.
- ▶ Apply the schema to the RDD of Rows via createDataFrame method provided by SparkSession.

**Given:**

```
case class Person(name: String, age: Int)
val peopleRdd = sc.textFile(...) // Assume RDD[Person]
```

# Creating DataFrames

## (1b) Create DataFrame from existing RDD, schema explicitly specified

```
// The schema is encoded in a string
val schemaString = "name age"

// Generate the schema based on the string of schema
val fields = schemaString.split(" ")
    .map(fieldName => StructField(fieldName, StringType, nullable = true))
val schema = StructType(fields)

// Convert records of the RDD (people) to Rows
val rowRDD = peopleRDD
    .map(_ .split(","))
    .map(attributes => Row(attributes(0), attributes(1).trim))

// Apply the schema to the RDD
val peopleDF = spark.createDataFrame(rowRDD, schema)
```

# Creating DataFrames

## (2) Create DataFrame by reading in a data source from file.

Using the SparkSession object, you can read in semi-structured/structured data by using the read method. For example, to read in data and infer a schema from a JSON file:

```
// 'spark' is the SparkSession object we created a few slides back  
val df = spark.read.json("examples/src/main/resources/people.json")
```

# Creating DataFrames

## (2) Create DataFrame by reading in a data source from file.

Using the SparkSession object, you can read in semi-structured/structured data by using the read method. For example, to read in data and infer a schema from a JSON file:

```
// 'spark' is the SparkSession object we created a few slides back  
val df = spark.read.json("examples/src/main/resources/people.json")
```

**Semi-structured/Structured data sources Spark SQL can directly create DataFrames from:**

- ▶ JSON
- ▶ CSV
- ▶ Parquet
- ▶ JDBC

*To see a list of all available methods for directly reading in semi-structured/structured data, see the latest API docs for DataFrameReader:*

<http://spark.apache.org/docs/latest/api/scala/index.html#org.apache.spark.sql.DataFrameReader>



# SQL Literals

Once you have a DataFrame to operate on, you can now freely write familiar SQL syntax to operate on your dataset!

# SQL Literals

Once you have a DataFrame to operate on, you can now freely write familiar SQL syntax to operate on your dataset!

## Given:

A DataFrame called `peopleDF`, we just have to register our DataFrame as a temporary SQL view first:

```
// Register the DataFrame as a SQL temporary view
peopleDF.createOrReplaceTempView("people")
// This essentially gives a name to our DataFrame in SQL
// so we can refer to it in an SQL FROM statement
```

# SQL Literals

Once you have a DataFrame to operate on, you can now freely write familiar SQL syntax to operate on your dataset!

## Given:

A DataFrame called `peopleDF`, we just have to register our DataFrame as a temporary SQL view first:

```
// Register the DataFrame as a SQL temporary view
peopleDF.createOrReplaceTempView("people")
// This essentially gives a name to our DataFrame in SQL
// so we can refer to it in an SQL FROM statement

// SQL literals can be passed to Spark SQL's sql method
val adultsDF
  = spark.sql("SELECT * FROM people WHERE age > 17")
```

# SQL Literals

The SQL statements available to you are largely what's available in HiveQL. This includes standard SQL statements such as:

# SQL Literals

The SQL statements available to you are largely what's available in HiveQL. This includes standard SQL statements such as:

- ▶ SELECT
- ▶ FROM
- ▶ WHERE
- ▶ COUNT
- ▶ HAVING
- ▶ GROUP BY
- ▶ ORDER BY
- ▶ SORT BY
- ▶ DISTINCT
- ▶ JOIN
- ▶ (LEFT|RIGHT|FULL) OUTER JOIN
- ▶ Subqueries: `SELECT col  
FROM ( SELECT a + b AS  
col from t1) t2`

Supported Spark SQL syntax:

[https://docs.datastax.com/en/datastax\\_enterprise/4.6/datastax\\_enterprise/spark/sparkSqlSupportedSyntax.html](https://docs.datastax.com/en/datastax_enterprise/4.6/datastax_enterprise/spark/sparkSqlSupportedSyntax.html)

For a HiveQL cheatsheet:

<https://hortonworks.com/blog/hive-cheat-sheet-for-sql-users/>

For an updated list of supported Hive features in Spark SQL, the official Spark SQL docs enumerate:

<https://spark.apache.org/docs/latest/sql-programming-guide.html#supported-hive-features>

# A More Interesting SQL Query

Let's assume we have a DataFrame representing a data set of employees:

```
case class Employee(id: Int, fname: String, lname: String, age: Int, city: String)
```

```
// DataFrame with schema defined in Employee case class
```

```
val employeeDF = sc.parallelize(...).toDF
```

# A More Interesting SQL Query

Let's assume we have a DataFrame representing a data set of employees:

```
case class Employee(id: Int, fname: String, lname: String, age: Int, city: String)
```

```
// DataFrame with schema defined in Employee case class
```

```
val employeeDF = sc.parallelize(...).toDF
```

Let's query this data set to obtain just the IDs and last names of employees working in a specific city, say, Sydney, Australia. Let's sort our result in order of increasing employee ID.

**What would this SQL query look like?**

# A More Interesting SQL Query

Let's assume we have a DataFrame representing a data set of employees:

```
case class Employee(id: Int, fname: String, lname: String, age: Int, city: String)
```

```
// DataFrame with schema defined in Employee case class
```

```
val employeeDF = sc.parallelize(...).toDF
```

*registered "employees"*

```
val sydneyEmployeesDF  
  = spark.sql("""SELECT id, lname  
                  FROM employees  
                  WHERE city = "Sydney"  
                  ORDER BY id""")
```



# A More Interesting SQL Query

Let's assume we have a DataFrame representing a data set of employees:

```
case class Employee(id: Int, fname: String, lname: String, age: Int, city: String)
```

```
// DataFrame with schema defined in Employee case class
```

```
val employeeDF = sc.parallelize(...).toDF
```

```
val sydneyEmployeesDF  
  = spark.sql("""SELECT id, lname  
                  FROM employees  
                  WHERE city = "Sydney"  
                  ORDER BY id""")
```

**Pretty simple.**

# A More Interesting SQL Query

Let's visualize the result on an example dataset.

**Given:**

```
val employeeDF = sc.parallelize(...).toDF
```

```
// employeeDF:      "employees"  
// +---+-----+-----+---+-----+  
// | id|fname|  lname|age|    city|  
// +---+-----+-----+---+-----+  
// | 12|  Joe|  Smith| 38|New York|  
// |563|Sally|  Owens| 48|New York|  
// |645|Slate|Markham| 28|  Sydney|  
// |221|David| Walker| 21|  Sydney|  
// +---+-----+-----+---+-----+
```

# A More Interesting SQL Query

Let's visualize the result on an example dataset.

## Given:

```
val employeeDF = sc.parallelize(...).toDF
```

```
val sydneyEmployeesDF  
  = spark.sql("""SELECT id, lname  
                  FROM employees  
                  WHERE city = "Sydney"  
                  ORDER BY id""")
```

Result ↴

```
// employeeDF:  
// +---+-----+-----+---+-----+  
// | id|fname|  lname|age|    city|  
// +---+-----+-----+---+-----+  
// | 12|  Joe|  Smith| 38|New York|  
// |563|Sally|  Owens| 48|New York|  
// |645|Slate|Markham| 28|  Sydney|  
// |221|David| Walker| 21|  Sydney|  
// +---+-----+-----+---+-----+
```

```
sydneyEmployeesDF:  
+---+-----+  
| id|  lname|  
+---+-----+  
|221| Walker|  
|645|Markham|  
+---+-----+
```

*Note: it's best to use Spark 2.1+ with Scala 2.11+ for doing SQL queries with Spark SQL.*